

## **INSTALLATION\_FILES File**

### **A List of the Files Involved in the Installation Process**

#### **Files Downloaded with the Source Code & 'Boilerplate' Files**

These files are generated by the GNU Autotools process and appear with the source code files when they are extracted :

- compile,
- config.guess,
- config.h.in.
- config.sub,
- configure,
- configure.ac,
- depcomp,
- install-sh,
- Makefile.am (a file this of this name also appears in subdirectories),
- Makefile.in (a file this of this name also appears in subdirectories),
- missing,
- mkinstalldirs.

The above files are required for both the Raquel DBMS and the Raquel GUI/Teaching Tool. In addition the latter has the file :

- SoftlinkToTclTk.sh (a bash script)

#### **Files Resulting From the Installation Process**

These files are generated during the Autotools compilation and installation process :

- config.h,
- config.status (this is created & used by the 'configure' script file),
- config.cache,
- config.log,
- Makefile (a file this of this name also appears in subdirectories),
- stamp-h1.

These files are generated in the case of both the Raquel DBMS and the Raquel GUI/Teaching Tool. In addition, 'SoftlinkToTclTk.sh' generates the following 2 softlinks :

- libtcl.so (a softlink pointing to the Tcl runtime file),
- libtk.so (a softlink pointing to the Tk runtime file).

**All of these files can be ignored by the user.**

There can be slight variations in these lists of (ignorable) files, depending on the specific installation.